



Vacuum consolidation

Design and case studies

Jérôme Racinais

Vice-Chairman of ISSMGE TC211 – Ground Improvement

Menard Engineering Director

jerome.racinais@menard-mail.com

29-May-20 Vacuum consolidation: Design and case studies

INTERNATIONAL WEBINAR

Ground Improvement
Techniques for Highway
Construction

MAY 29 – 30, 2020
10.00 -14.00 (IST)



Organized by
Geotechnical Engineering Division
CSIR-Central Road Research Institute
New Delhi, India

Supporters



Contents


01 Introduction

02 Menard Vacuum Consolidation

03 Case study #1 : A837 Highway in France (1993)

04 Case study #2 : New Mexico City Airport (2018)

05 Conclusions



01


Introduction

Introduction

4


Ground improvement techniques

- ⊕ **Densification by direct action on the soil structure**




Ground reinforcement techniques

- ⊕ **Global improvement of performance by installation of inclusions**




Introduction

5




Introduction

6



Menard Vacuum System

7




02

Menard Vacuum Consolidation


Menard Vacuum Consolidation

9



Menard Vacuum Consolidation


10



The air and water pumping system is installed and creates vacuum in the soils below the impervious membrane equivalent to a depression **between 60 and 80 kPa**, depending on the global efficiency of the system.

Menard Vacuum Consolidation


11





Menard Vacuum Consolidation

12

Classical preloading






Vacuum preloading



Menard Vacuum Consolidation



13

Classical preloading



$$\sigma' = \sigma - u$$

Vacuum preloading



03

Case study #1

A837 Highway in France (1993)

A837 Highway (1993-1994)

17



○ A837 project (1993-1994) – Rochefort to Saintes

Total length of section : 37,5 km
10 km go through marshy zones with fill from 2,0 m to 8,0 m high

• Current sections

Classical preloading with vertical drainage

Prefabricated band drains (10 cm)

Grid : from 1,00 to 1,60 m

Depth : from 10 to 25 m

• Critical sections (bridge access embankments)

Menard Vacuum Technique as an alternative solution to preloading+drains+stone columns+berms

Soil conditions and technical specifications


18

Section	(1) Tonnay Charente	(2) Boutonne	(3) Agnet
Thickness of soft soil	18 to 26 m	4 to 13 m	4 to 20 m
Height of fill above ground level	2 m	5 to 8 m	6 m
Settlement criterion	10 cm after 30 years		

	Undrained Shear Strength Su	Void ratio e	Compression index Cc	Swelling index Cs	Creep index C_{αe}	Coeff. of vertical consolidation Cv	Coeff. of horiz. consolidation Ch
Soft clay	15 kPa	1,99	1,24	0,079	0,068	10 ⁻⁷ m ² /s	7 x 10 ⁻⁷ m ² /s

Sequence of works


19



- Placing a free drainage sand blanket (0,5 to 1,0 m thickness) in order to provide a suitable working platform
- Installation of vertical drains
- Installation of an horizontal drains network
- Installation of monitoring
- Excavation of trenches
- Installation of membrane
- Connection of drainage system to the pumps and beginning of pumping
- Add fill (to reach the final level and to compensate the expected settlement)

Installation of vertical drains and horizontal drains

20



Preparation of peripheral sealing trenches

21



Installation of membrane

22



29-May-20

menard

Monitoring of consolidation – Settlement plates and piezometers

23



Connection of drainage system to the pumps and beginning of pumping

24



Some pictures

25



Tonnay Charente swamp area with 2 m high fill on membrane



Boutonne River crossing (One zone is simply under vacuum, the other one is already filled)


Results

26

With Menard Vacuum Consolidation, no more temporary surcharge.

The fill is placed directly on the membrane under vacuum up to final elevation increased only by the height of expected settlement during consolidation.

Historique





27

A837 SUPPRESSIONS INTERSTITIELLES modifiées Profil 248 +10
REMBLAI DE TONNAY-CHARENTE.ZONE "DAURADE-RD911"

Unité Technique Géotechnique-Mesures


TEMPS en jours

PROFIL ELECTRIQUE



Inclinometer results

The embankment is on the left; there is a 10 cm inwards horizontal displacement due to horizontal consolidation.



Conclusions

30

Advantages of Menard Vacuum solution

- Quicker embankment construction without any circular failure risk (6 to 9 months instead of 18 months)
- No more lateral berm
- Decreased volume of earthmoving (no more temporary surcharge)
- Better control of settlement with time

04

Case study #2

New Mexico City Airport (2018)

The New Mexico City International Airport (NAICM)


32

The NAICM was partially built when it was abruptly canceled in late 2018 after a popular consultation. Instead, the current Federal government of Mexico plans to build an international airport at Santa Lucía Air Force Base north of the city.

1st phase in operation: **October 2020**
Total area: **4 430 hectares**
X-shaped terminal: **743,000 m²**
Runways: **3**
Passengers per year: **68 millions**

Soil conditions

33



29-May-20

Vacuum consolidation: Design and case studies

Soil conditions

34



NAICM




Soil conditions

35

Plataforma de Tezontle
NAF ~ 1.10 m
Hundimiento reg prom ~ 24 a 32 cm/año


FAS (Formación arcillosa superior) con intercalaciones de arenas y cenizas volcánicas)
Arcillas CH

Capa dura (CD)



Soil conditions

36



Ground improvement works

37



Prefabricated Vertical Drains and Preloading under Runway II

38



Prefabricated Vertical Drains and Preloading under Runway II

39




Ground improvement works

40



Menard Vacuum Trial Area - Execution

41




Working platform
 $0,5\text{ m} + 0,5\text{ m} = 1\text{ m}$ of "tezontle" ($13,7\text{ kN/m}^3$)



Monitoring installation

Menard Vacuum Trial Area - Execution

42



Menard Vacuum Trial Area - Execution

43




Before Vacuum



After beginning of Vacuum

Menard Vacuum Trial Area - Execution

44




29-May-20

Vacuum consolidation. Design and case studies



Menard Vacuum Trial Area - Execution

45



Results – Vacuum Pressure

46




Atmospheric pressure = **78 kPa** at the Texcoco Lake (2228 m a.s.l)

Vacuum pressure = **72 kPa** in the soil at the beginning

Vacuum pressure = **60 kPa** in the soil after 6 months


Results – Pore Water Pressures

47




Results – Settlements

48




Results – Settlements



49


Results – Settlements and extracted water

50



Volume of extracted water
 $V_{\text{water}} = 9\,353\text{ m}^3$

Results – Settlements




Volume of extracted water

$$V_{\text{water}} = 9\,353 \text{ m}^3$$

Volume of settlement


$$V_{\text{settlement}} = 9\,628 \text{ m}^3$$



The amount of extracted water is equal to the total settlement. Menard Vacuum Consolidation method has nothing to do with dewatering.



Results – Lateral displacements

52




Menard Vacuum Trial Area vs Drain to Drain Trial Area

53




Menard Vacuum Trial Area vs Drain to Drain Trial Area

55



Differential settlements along the transverse centerline

Fig.10 summarizes data obtained from the horizontal inclinometer. Curves evidence isochronic settlement profiles that have almost symmetrical shapes and trends similar to that exhibited by traditional embankments. The differential settlements between the center and the boundaries of the embankment are influenced by the inward movements of the lateral boundaries caused by vacuum. Boundary settlements vary linearly with the corresponding ones detected at the centre. Along the transverse centerline a ratio equal to 0.6 between lateral and central settlements was observed: this value is practically coincident with that predicted by the elastic theory for traditional embankments.





Settlements
2,00 m at the centre
1,20 m at the edges

Fig 10 – Time history of settlements measured by horizontal inclinometer

Menard Vacuum Trial Area vs Drain to Drain Trial Area

56





Drain to Drain method
1,98 m in 6 months

This aerial photograph shows a large-scale construction project in a flat, arid landscape. The site is divided into several rectangular treatment areas. On the left, a large rectangular area is labeled 'Drain to Drain method' with a result of '1,98 m in 6 months'. This area shows a dark, reddish-brown soil surface with some internal drainage patterns. In the center, there is a cluster of small, white, rectangular structures, likely temporary site offices or equipment storage. To the right, another large rectangular area is labeled 'Menard Vacuum' with a result of '2,90 m in 6 months'. This area is also dark reddish-brown but appears more uniform in color and texture. A long, narrow, winding channel of dark soil runs along the bottom edge of the site. The surrounding landscape is dry and covered with sparse, low-lying vegetation. A road or track is visible at the top of the image.

Menard Vacuum
2,90 m in 6 months

Bibliography

58

Cognon, J.M. (1991). La consolidation atmosphérique. Vacuum consolidation. *Revue Française Géotechnique*, n°57, pp. 37-47

Ghionna, V.N. et al. (2018). Vacuum preloading with drain to drain method for the New International Airport of Mexico City. *DFI-EFFC International Conference on Deep Foundations and Ground Improvement*, Rome, Italy.

Juarez Velazquez, L.D. and Cirion Arana, A. (2018). Vacuum Consolidation with impervious membrane Soil Improvement System (Atmospheric Consolidation System). Test panel case study made for Mexico's New International Airport (NAIM) in Texcoco, Mexico. *XXIX Reunión Nacional de Ingeniería Geotécnica*, León, Mexico

05

Conclusions

Conclusions

60

Vacuum consolidation is an effective means for improving highly compressible soft soils.

- The Vacuum Consolidation method uses the **site atmospheric pressure** to pre-load an **impermeable soil** in order **to anticipate long-term surface deformations** and to “prepare” the soil to withstand the future service loads.
- Vacuum consolidation can yield an effective equivalent preload of about **3 to 5 m of conventional surcharge**;
- Vacuum consolidation allows to **accelerate the consolidation process** as compared to conventional stage-loading because it **reduces drastically the risk of failure**;
- It can be **easily combined with classical preloading**;
- As compared to classical preloading, the Vacuum pressure acts homogeneously throughout the soil mass, without **any reduction in depth or width**.